

Model	0.25	0.5	1.0	2.0	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	12.5
D1 (mm)	219	300	500	600	600	800	900	900	1000	1000	1200	1200	1300
D2 (mm)	325	400	600	700	700	900	1000	1000	1100	1100	1300	1300	1450
L (mm)	650	800	900	1350	1850	1830	2010	2370	2460	2750	2600	2900	3200
S (mm)	385	425	650	845	845	880	905	400	430	430	470	470	470
B (mm)	185	205	265	545	545	650	675	675	680	680	750	750	750
C (mm)	900	1155	1225	1380	1380	1550	1665	1665	1740	1740	2000	2100	2200
H (mm)	2150	2615	3070	4150	4650	4940	5275	5145	5335	5630	5840	6250	6800
h (mm)	330	350	365	475	475	475	475	650	650	650	660	680	680
Heat exchange area (m ²)	0.31	0.57	1.08	2.16	3.13	4.04	5.11	6.15	7.13	8.17	9.09	10.25	12.9
Motor power (K=W)	0.75	1.5	1.5	2.2	3	4	5.5	5.5	5.5	7.5	7.5	7.5	11
Weight (kg)	245	385	475	1090	1495	1810	2370	2460	2800	3100	4000	4500	4900